

Chain and ring steel, railway vehicle steel, fasten piece and oil pumping rod steel

Name	Steel grade	Diameter	Carried standard	Application
chain and ring steel	HZR3、HZR3S、HZR4、CM490(AM2)、CM690(AM3)、20MnV、25MnV、23MnSiV	φ12~230	GB/T20848 、GB/T 18669 CCS》、GB/T 10560	Mooring cable, anchor chain, high strength ring chain for mining
railway vehicle steel	ER6 (I) 、 (II) 、 (III) , ER7 (I) 、 (II) 、 (III) , ER8 (I) 、 (II) 、 (III) , ER9 (I) 、 (II) 、 (III) , CL60(H), CL60, LZ50、SSW(III), C(I)、 (II) , B(I)、 (II) , R73, SSW, 25MnCrNiMoA、AAR-D、LZ50	CCM billet φ380、 φ450、 φ500、 φ600、 φ700、 φ800, Slab φ140、 φ160、 200×200、 230×230、 250×250	Sign the technical specification with Ministry of railways and international client	Railway vehicle wheel, shaft, coupler knuckle, coupler yoke, brake beam
Fasten piece and oil pumping rod steel	B7、10B21、35ACr、SCM435、A5194140、35Mn2A、40Mn2A、20CrMoA~42CrMoA、ZC35CrMoA	φ12~300	YB/T054 GB/T 6478 Corresponding international standard Technical specification	Bolt, nut, rivet etc. petroleum pumping rod

Produced by Jiangsu Shagang Group Huaigang Special Steel Co., Ltd